

隆基隆行 LONGi PARK™

## PV-Storage-Charging Integrated Green Tram Station

**PV Roof** | Car shelter and stable power station

**Module Installation** | Standardized components  
Free of engineering machinery installation

**Quality Assurance** | LONGi quality Wind and  
seismic resistance

EMPOWER EVERY INCH OF  
OUR BUILDING TO

**Generate**  
**ELECTRICITY**

## Green energy and industrial aesthetics

Green energy charging and car shelter  
Smart display and traffic carrier  
Industrial aesthetics and minimalistic

## Factory prefabrication and quick delivery

Standard product and modular design  
Free of welding, noise and dust  
Aluminum alloy parking spaces are free of installation

## Free selection and intelligent management

PV-storage-charging optional  
Visible electric energy information data  
Customized color

## Quality assurance


LONGi high-efficiency monocrystalline module  
High-quality building materials, Grade A fireproof  
Bifacial and double-glazed, efficient power generation

## LONGi PARK standard design parameters

## The W-type optical storage

Design parameters of the W-type optical storage and charging and parking system

Product model	LSC-W-XX-C
Component configuration	LONGi Hi-MO4 efficient two-sided half-chip component
Inverter	Multiple route MPPT group serial inverter
Monitoring mode	Mobile APP or PC cloud monitoring
Structural system	6005-T6 high-strength aluminum alloy
Service lifeCharging pile	25-year design life
Energy storage	Energy storage system can be selected according to customer requirements
Charging pile	Charging pile can be selected according to customer requirements
Parallel cage	Outdoor type, meeting the requirements of Local Power Supply Bureau
Notes	It can be adjusted according to charging station planning




\*The above parameters are for reference only, and the specific project design and actual supply shall prevail.

## LONGi PARK standard design parameters

## The Y-type optical storage

Y型光储充泊车系统设计参数

Product model	LSC-Y-XX-C
Component configuration	LONGi Hi-MO4 efficient two-sided half-chip component
Inverter	Multiple route MPPT group serial inverter
Monitoring mode	Mobile APP or PC cloud monitoring
Structural system	Steel structure, surface fluorocarbon coating
Service lifeCharging pile	25-year design life
Energy storage	Energy storage system can be selected according to customer requirements
Charging pile	Charging pile can be selected according to customer requirements
Parallel cage	Outdoor type, meeting the requirements of Local Power Supply Bureau
Notes	It can be adjusted according to charging station planning



\*The above parameters are for reference only, and the specific project design and actual supply shall prevail.